





Order form Orderer Valid from November 2018 Order no.

## DMT143L Dewpoint Transmitter (DMT242 Replacement)

|  |  | PRICE |
|--|--|-------|
| <ol> <li>Sensor and thread type</li> </ol> | ISO G1/2" Probe with DRYCAP®180M Sensor L  |       |
|  | NPT 1/2" Probe with DRYCAP®180M Sensor P   |       |
|  | ISO G1/2" Probe with DRYCAP®180S Sensor R  |       |
|  | NPT 1/2" Probe with DRYCAP®180S Sensor T   |       |
| 2 Digital interface                        | RS485 1  |       |
|  | Modbus RTU (defaults: 19200, N, 8, 2, address 240) 2   |       |
| 3 Analog signal output                     | None 0 0 0   |       |
|  | 420mA         (3.6 mA error state)         C         I<      |       |
|  | 420mA (0 mA error state) G   |       |
| 4 Analog output scaling                    | None, metric units (analog signal output selection must be none) 0   |       |
|  | -80+20°C Td (same as DMT242A scale) 1  |       |
|  | -80+20°C Tda, dewpoint at ambient pressure 2 2 2   |       |
| NOTE: Please select U                      | -60+60°C Td (same as DMT242B scale) A  |       |
| if <u>non-metric</u> units (°F)            | -50+50°C Td (same as DMT242S scale) B  |       |
| are needed for analog                      | 01000 ppmv 3   |       |
| and/or digital output                      | 05000 ppmv 4   |       |
|  | free scaling ppm Define scale: P   |       |
|  | free scaling Td °F Define scale: U   |       |
|  | free scaling Td °C         Define scale:         X         I <thi< th="">         I</thi<> |       |
|  | free scaling %RH Define scale: N   |       |
| 5 Alarm LED setpoint                       | Off Only fault indication A  |       |
|  | -40°C Td Class 2 B   |       |
|  | -20°C Td Class 3 C   |       |
|  | -10°C Td D   |       |
|  | +3°C Td Class 4 E  |       |
|  | Other value define value: °C Td X  |       |
|  | Deactivated LED always off Z   |       |
| 6 Process gas                              | Air for DRYCAP®180M Default setting with 24 h purge interval 1   |       |
| and chemical purge                         | Air for DRYCAP®180S Original setting with DMT242S, no purge E  |       |
| settings                                   | Air for DRYCAP®180S with 12h purge interval, recommended F   |       |
| 7 Pressure setting                         | 1 bar (abs) A A A A A A A A A A A A A A A A A A A  |       |
| for optimized                              | 3 bar (abs) B  |       |
| accuracy                                   | 5 bar (abs) C C C  |       |
|  | 7 bar (abs) D D  |       |
|  | special (max 20 bar abs) Define value: bar X   |       |
| 8 Cable                                    | No cable 0   |       |
|  | 0.3 m (1.0 ft) spare: HMP50Z032 2  |       |
|  | 3 m (9.8 ft) spare: HMP50Z30A 3  |       |
|  | 5 m (16.4 ft) spare: HMP50Z500 4   |       |
|  | 10 m (32.8 ft) spare: HMP50Z1000 5   |       |
|  | 1.5 m (4.9 ft) heavy duty cable spare: 225777 6  |       |
|  | 3 m (9.8 ft) heavy duty cable spare: 225229 7  |       |
| 9 Sensor protection                        | Stainless steel sintered filter (38um) spare: HM47280SP 1  |       |
|  | Stainless steel filter for vacuum spare: HM47453SP S S   |       |
| 0 Accessories                              | no accessories 0   |       |
|  | DMT242 to DMT143 cable adapter (spare: 247890SP) A   |       |
| ONLY for ISO1/2" thread                    | Basic sampling cell DMT242SC   |       |
|  | Sampling cell with swagelok 1/4" male connectors DMT242SC2 2   |       |
|  | Sampling cell with quick connector and leak screw, DSC74 3   |       |
|  | Two pressure sampling cell, DSC74B 4   |       |
|  | Two pressure sampling cell with cooling/venting coil, DSC74C 5   |       |
|  | Duct installation flange DM240FA 6   |       |
|  | Mounting nut 7   |       |
|  | NPT 1/2" adapter (spare: 210662SP) 8   |       |
| 1 Package                                  | Standard A   |       |
| 12 Identity                                | Vaisala S  |       |
| 13 User guide language                     | no user guide A  |       |
| see guide language                         | multilingual guide X   |       |
|  | TOTAL  |       |
|  | QTY  |       |
|  |  |       |

Selections in bold are included in the prices of the basic versions. Selections in italic are available at an extra price.

Example of order code with typical settings: DMT143 L 1 C 1 A 1 A 3 1 0 A S X

|  | Replacement | DMT242A | L | 1 | С | 1 | Ζ | 1 | Α | 0 | 1 | Α | Α | S | X |
|--|-------------|---------|---|---|---|---|---|---|---|---|---|---|---|---|---|
| DMT143 DMT242S R 1 C B Z F A 0 1 A A S 2 | Examples:   | DMT242B | Г | 1 | С | Α | Ζ | 1 | Α | 0 | 1 | Α | Α | S | X |
|  | DMT143      | DMT242S | R | 1 | С | в | Ζ | F | Α | 0 | 1 | Α | Α | s | Х |

End customer: