

LP384-M12E Series



VIBRATION ANALYSIS HARDWARE

Loop Power Sensor, 4-20 mA Output Proportional to Vibration in Acceleration, Side Exit 4 Pin M12 Connector, M8x1.25 Captive Bolt




Product Features

4-20 mA Current Proportional to Vibration in Acceleration

- ▶ Peak and RMS Outputs Available
- ▶ Transmits Signals Over Long Distances with No Signal Loss
- ▶ Outputs to PLC, DCS, SCADA

LP384-XXX-M12E 4 Pin M12 Connector

Connector Pin	Polarity
1	(+) Loop Power mA Output
2	(-) Common
3	Not Used
4	Not Used



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	LP384-M12E		Physical		
Tolerance: 4 mA	(± 10%)		Sensing Element	Welded, Hermetic	
Tolerance: 20 mA	(± 10%)		Sensing Structure	Shear Mode	
Electrical			Weight	4.9 oz	140 grams
Settling Time	<60 Seconds		Case Material	316L Stainless Steel	
Voltage Source (IEPE)	15-30 VDC		Mounting Thread	M8x1.25 Captive Bolt	
Case Isolation	>10 ⁸ ohm		Connector (Non-Integral)	2 Pin MIL-C-5015	
Environmental			Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Operating Temperature Range	-4 to 212 °F	-20 to 100 °C	Mounting Hardware Supplied	1/4-28 Captive Bolt	M8x1.25 Captive Bolt
Electromagnetic Sensitivity	CE		Calibration Certificate	Current Output @ 100 Hz	
Submersible Depth	200 ft.	60 m			

Ordering Information