


LP812-XXX-5XC Series



VIBRATION ANALYSIS HARDWARE

Low Capacitance, Intrinsically Safe Loop Power Sensor, 4-20 mA Output Proportional to Vibration in Velocity, Top Exit with Flying Leads



Product Features


Continuous Monitoring in Hazardous Locations

Velocity 4-20 mA Output for Applications in Hazardous Locations

- ▶ CSA and ATEX Approvals
- ▶ Intrinsic safe applications with use of barrier
- ▶ With 1 inch NPT conduit fitting, Integral 1/4 - 18 NPT Mounting Stud

LP812-XXX-51C 1/4 inch NPT Mount


Conductor	Polarity
Red	(+) Loop Power mA Output
Black	(-) Common



Built To Order

LP812-XXX-52C 1/2 inch NPT Mount

Conductor	Polarity
Red	(+) Loop Power mA Output
Black	(-) Common



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Tolerance: 4 mA	(± 10%)		Physical		
Tolerance: 20 mA	(± 10%)		Sensing Element	PZT Ceramic	
Electrical			Sensing Structure	Shear Mode	
Settling Time	<60 Seconds		Weight	12 oz	340 grams
Voltage Source (IEPE)	12-28 VDC		Case Material	316L Stainless Steel	
Case Isolation	>10 ⁸ ohm		Mounting Thread	1/4 NPT (LP812-51C)	
Environmental				1/2 NPT (LP812-52C)	
Operating Temperature Range	-4 to 176°F	-20 to 80°C	Connector (Non-Integral)	Flying Leads	
Electromagnetic Sensitivity	CE		Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Sealing	IP68		Calibration Certificate	Current Output @ 100 Hz	

Ordering Information

LP - -